

# Entrance and French Doors

**Max Door Size** 

96" x 144"

### **Features**

- · 9/16" laminated glass or 1 5/16" insulated laminated glass
- · Design Pressure: +100/-100
- · Emtek Hardware, Ladder Pull and Smart Lock options
- · ADA bumper threshold
- · Custom inserts available
- · Optional Sidelite or Transom
- · Low-E or Tinted glass



# Pivot Door

**Max Door Size** 

78" x 120"

### **Features**

- · Design Pressure: +100/-100
- · All stainless, European pivots High-grade stainless-steel assembly fasteners
- · Ladder pull handles up to 8 feet
- · Optional Sidelite or Transom
- · Low-E or Tinted glass



## Sliding Doors Standard and Slim line

**Panel Size** 

62.75" x 150"

### **Features**

- · 9/16" single-glazed glass or 1" insulated laminated glass
- · Design Pressure: +80/-105
- · Non-Pocket, Pocket and 90° Corner **Options**
- · Crest handles
- · Stainless steel with large nylon rollers
- · Standard Sill rise 3.5" or Low Sill Rise 1.75"
- · Slim Line Option 1 1/4" Sightline with Front line view of 1"
- · Low-E or Tinted glass



STANDARD COLOR VARIATIONS

White, Black, Bronze





### Casement

Operable, Fixed and **Awning** 

**Max Size Operable** & Awning

48" x 84"

**Max Size Fixed** 

72" x 72" or 54" x 96"

### Maxiview

**Max Size Single Panel** 97" x 157"

**Max Size Multiple Panel** 94" x 157"

## **Frontset**

**Max Size Single Panel** 75.5" x 180"

Max Size Multiple Panel 60" x 144" or 72" x 120"

## Single-Hung

**Max Size Standard** 53 1/8" x 76"

**Max Size Hi-Rise** 53 1/8" x 77"

#### **Features**

- · 5/16" laminated, 7/16" laminated or 11/16" insulated laminated
- · Design Pressure: +80/-85
- · Flanged or equal frame installation
- · Low rise sill frame for slimmer interior sight lines
- · 45-degree mitered corners with European corners keys for flush alignment of frame and sash
- · Single acting lock with hidden multi-point keepers
- · Available in single or double vent configuration
- · Low-E or Tinted glass

### **Features**

- · Triple 1 3/16" or 15/16" laminated
- · 1 1/8" x 3 1/2" profile plus 1 1/8" front set
- · Design Pressure: +90/-90
- · Mullin free impact glass
- · Glass to glass butt joints
- · 35-degree angle or greater
- · Low-E or Tinted glass

#### **Features**

- · 1.50" x 4.50" profile plus 3/4" front set
- · Design Pressure: +120/-135
- · Flush stop available for 9/16" glass
- · Can be thermally broken
- · Low-E or Tinted glass

### **Features**

- · 7/16" laminated or 11/16" insulated laminated
- · Design Pressure: +120/-135
- · Multiple Locking Options
- · Standard sill option without anchor on the bottom
- · Installation screws protected by a cover
- · Low-E or Tinted glass



STANDARD COLOR VARIATIONS

White, Black, Bronze

